

Standard Features

- **Print, Fold and Seal:** One-step process eliminates excess document handling
- **Document Security:** Enclosed paper path from the printer to pressure sealer ensures security. Ideal for PIN notices or other confidential applications
- **Form Capabilities:** Processes forms up to 14" in length
- **Printer Compatibility*:** Designed to work with HP/Troy P2015, P3005, P4014, 4200, 4250 & 4350 and Lexmark/Source T640 laser printers. A list of other compatible models is available.
- **Installation:** Easy to install, no software required
- **Alignment Base:** Special alignment base holds the printer and pressure sealer securely and slides apart for easy access to the paper path and fold plates
- **Fold Types:** Folds Z, C**, Half and custom folds
- **LED Control Panel:** Notifies operator when the power is on, a cover is open, the paper runs out, or if a fault occurs
- **Fault Detector:** Detects double feeding and any faults
- **Dedicated Use:** Designed for in-line use only
- **Six-Digit Resettable Counter**

Options:

- **P2000IL:** Cost-saving package that includes FD 2000IL System, 18" conveyor and 2 cabinets
- **18" Conveyor w/Photo Eye:** Allows for neat and sequential stacking
- **Locking Cabinets:** Fully enclosed for storage (2 cabinets required)

* See reverse for complete printer specifications

** C-Fold bottom check position only

Formax

New Hampshire, USA
www.formax.com

LOCAL DEALER:



FD 2000IL System shown with IL Pressure Sealer and IL Alignment Base, laser printer (not included), optional conveyor and optional locking cabinets

Secure Processing of One-Piece Mailers

The FD 2000IL System allows operators to print, fold and seal pressure-sensitive one-piece mailers in one step, reducing processing time while increasing document security. The IL System works in-line with model-specific MICR and Non-MICR desktop laser printers. The fully-enclosed paper path is designed to conceal confidential documents, including PIN notices, checks, school grade reports and health care information.

The IL System incorporates the industry-leading FD 2000 AutoSeal[®] which features a user-friendly LED control panel and pre-marked fold settings for 11" and 14" standard forms. The FD 2000IL is ideal for companies processing sensitive documents or those looking for a mid-volume in-line solution for processing pressure seal forms.

Flexible

The FD 2000IL System handles a variety of documents up to 8.5" x 14" including checks, invoices, school reports, tax forms and appointment notices. Pressure seal mailers can be used for virtually any application that can be printed on one form.

Easy to Operate

The AutoSeal® IL System is easy to install. An IL-compatible desktop laser printer (see Specifications, below) is placed on the IL-Alignment Base with the FD 2000IL pressure sealer using placement guides to ensure proper alignment. The IL Alignment Base incorporates an easy-pull system which allows the printer to be pulled away from the FD 2000IL to provide convenient access to the paper path and fold plates.

Powerful

The FD 2000IL processes up to 50,000 forms per month in a compact and powerful design. The user-friendly control panel features LED indicators and a six-digit resettable counter. The FD 2000IL is built in the USA with proven Formax strength and reliability.




User Friendly Control Panel



Enclosed paper path provides optimal document security

Pressure Seal Solution

The AutoSeal® FD 2000IL System, combined with a laser printer and pressure seal forms, creates a secure, time-saving and efficient solution for paper processing.



Standard "Z" Fold Process

Specifications:

Printer Compatibility: HP/Troy P3005, 4200, 4250, 4350 with two 500-sheet trays
HP/Troy P2015, with two 250-sheet trays (requires FD 2000-45IL Riser)
HP/Troy P2055, with one 500-sheet tray
HP/Troy P4014, with one 500-sheet tray (requires FD 2000-47IL Riser)
Lexmark/Source T640, with one 500-sheet tray (requires FD 2000-46IL Riser)
Xerox Phaser 4510 (requires FD 2000-55IL printer adapter kit)

Fold Types: Z & V (all applications), C (bottom check position only)

Speed: Printer dependent

Paper Size: Up to 8.5" W x 14" L

Power: FD Model: 120 Volts AC, 50/60 Hz
FE Model: 220 Volts AC, 50/60 Hz

Duty Cycle: Up to 50,000 pieces per month

Dimensions (closed) **: 19" W x 46" L x 23" H

Dimensions w/18" Conveyor (closed): 19" W x 65" L x 23" H

Tabletop Area Required: 20" W x 43" L

Tabletop Area Required w/18" Conveyor: 20" W x 69" L

Dimensions w/Cabinets & 18" Conveyor: 20" W x 74" L x 48" H



FD 2000-45IL Riser with HP/Troy P2015 Printer



Standard Catch Tray

** Dimensions include IL Pressure Sealer and IL Alignment Base (both included) and laser printer (not included in system)